



Smeermiddelenindustrie • Schmiermittelindustrie

Lube-oil industry • Industrie Lubrifiant

P.O. Box 1010
3300 CA Zwijndrecht
the Netherlands
Tel. +31(0)78 610 11 22
Fax. +31(0)78 610 22 20
Internet: <http://www.oliebron.com>
e-mail: info@oliebron.nl

Full Synthetic Motor Oil 0W30

Description

This sophisticated full-synthetic fuel economy universal motor oil is produced with high quality synthetic base oils with a high viscosity index and a well-balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

This universal fuel economy synthetic motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below.

Performance Level

ACEA A3/B4-12
API SH/CF
Meets the requirements of
MB 229.3/226.5
VW 502.00/505.00
BMW Longlife-01
Renault RN0700
API SN/CF *)
*) API SN quality only; not-licensable
due to phosphorus-limit

Typicals

Density at 15 °C, kg/l	0,848
Viscosity -35 °C, mPa.s	5400
Viscosity 40 °C, mm ² /s	56,60
Viscosity 100 °C, mm ² /s	10,20
Viscosity Index	170
Flash Point COC, °C	230
Pour Point, °C	-51
Total Base Number, mgKOH/g	10,3
Sulphate Ash, %	1,33