



Smeermiddelenindustrie • Schmiermittelindustrie

Lube-oil industry • Industrie Lubrifiant

P.O. Box 1010
3300 CA Zwijndrecht
the Netherlands
Tel. +31(0)78 610 11 22
Fax. +31(0)78 610 22 20
Internet: <http://www.oliebron.com>
e-mail: info@oliebron.nl

Full Synthetic Motor Oil SN/CF 5W40

Description

A nowadays universal full-synthetic motor oil, produced with synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

This universal synthetic motor oil, recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below.

Performance Level

ACEA A3/B4-12
API SN/CF
Meets the requirements of
MB 229.3/226.5
VW 502.00/505.00
BMW Longlife-01
Porsche A40
Renault RN0700/RN0710

Typicals

Density at 15 °C, kg/l	0,850
Viscosity -30 °C, mPa.s	4400
Viscosity 40 °C, mm ² /s	84,60
Viscosity 100 °C, mm ² /s	13,90
Viscosity Index	169
Flash Point COC, °C	232
Pour Point, °C	-54
Total Base Number, mgKOH/g	10,3
Sulphate Ash, %	1,33